MAINTENANCE PLANNING GUIDELINES

2006

ACTIVITY: Drainage (R316)

ACTION: Repair Curbing

A. Concrete Curbs

MAJOR & MINOR

DEFINITION: The time and expenses incurred for the installation, repair and maintenance of roadway drainage ditches, structures, and all slide repairs. This includes installing and maintaining pavement drainage systems.

PURPOSE: To restore drainage by repairing concrete curbs, islands, curb and gutters, and curbed medians.

SCHEDULING: As needed when the air and ground temperatures are above 45°F.



RECOMMENDED EQUIPMENT:

- Trucks
- Concrete Mixer or Concrete Mobile
- Concrete Curb Machine
- Concrete Saw
- Compressor/Breaker
- Water Tank
- Traffic Control Equipment: (See EPG 616.23 Traffic Control for Field Operations)

RECOMMENDED PROCEDURE:

- 1. Place traffic control devices as needed.
- 2. Saw exterior limits of damaged section.
- 3. Remove damaged concrete, form, install steel, and place expansion felt at each transverse joint.
- 4. Pour concrete, finish, and apply curing compound.
- 5. When cured, remove forms, backfill, and seed.
- 6. Clean work area.
- 7. Remove traffic control devices.

RECOMMENDED MATERIAL:

- Concrete
- Reinforcing Steel
- Form Material
- **Expansion Felts**
- Grates
- Water
- Seed
- Curing Compound

SAFETY: Be careful when working near traffic. Wear all appropriate PPE. Refer to the Safety Policies, Rules & Regulations – Employee Handbook...

OTHER CONSIDERATIONS: N/A

REFERENCES: Missouri Standard Specifications for Highway Construction Section; 609.10.