#### MAINTENANCE PLANNING GUIDELINES

2006

**ACTIVITY:** Drainage (R316)

**ACTION:** Repair Curbing *B. Asphalt Curbs* 

#### MAJOR & MINOR

**DEFINITION:** The time and expenses incurred for the installation, repair and maintenance of roadway drainage ditches, structures, and all slide repairs. This includes installing and maintaining pavement drainage systems.

**PURPOSE:** To restore drainage by repairing asphalt curbs, islands, and medians.

**SCHEDULING:** As needed when the air and ground temperatures are above 60°F.

J	F	M A R	Α	М	J	J	Α	s	0	N	D
Α	Ε	Α	Р	Α	U	U	U	Ε	С	0	E
N	В	R	R	Υ	N	L	G	Р	Т	٧	С

## **RECOMMENDED EQUIPMENT:**

- Trucks
- Air Compressor/Asphalt Bit
- Asphalt Curb Machine
- Distributor
- Traffic Control Equipment; (See EPG 616.23 Traffic Control for Field Operations)

### RECOMMENDED PROCEDURE:

- 1. Place traffic control devices as needed.
- 2. Remove damaged material, tack, repair, and compact area.
- 3. Backfill and seed as necessary.
- 4. Remove traffic control devices.

# **RECOMMENDED MATERIAL:**

- Hot Mix
- Liquid Asphalt (Tacking Grade)
- Seed

**SAFETY:** Be careful when working near traffic. Wear all appropriate PPE. Refer to the Safety Policies, Rules & Regulations – Employee Handbook..

OTHER CONSIDERATIONS: N/A

**REFERENCES:** Missouri Standard Specifications for Highway Construction Section; 609.3.