MAINTENANCE PLANNING GUIDELINES

2/2014

ACTIVITY: Drainage (R316)

ACTION: Repair Curbing

A. Concrete Curbs

MAJOR & MINOR

DEFINITION: The time and expenses incurred for the installation, repair and maintenance of roadway drainage ditches, structures, and all slide repairs. This includes installing and maintaining pavement drainage systems.

PURPOSE: To restore drainage by repairing concrete curbs, islands, curb and gutters, and curbed medians.

SCHEDULING: As needed when the air and ground temperatures are above 45°F.

J	F	М	Α	М	J	J	Α	S	0	N	D
Α	Ε	A R	Р	Α	U	U	U	Ε	С	0	Ε
N	В	R	R	Υ	Ν	L	G	Р	Т	٧	C

RECOMMENDED EQUIPMENT:

- Trucks
- Concrete Mixer or Concrete Mobile
- Concrete Curb Machine
- Concrete Saw
- Compressor/Breaker
- Water Tank
- Traffic Control Equipment; (See EPG 616.23 Traffic Control for Field Operations)

RECOMMENDED MATERIAL:

- Concrete
- Reinforcing Steel
- Form Material
- Expansion Felts
- Grates
- Water
- Seed
- Curing Compound

RECOMMENDED PROCEDURE:

- 1. Contact Dig Rite and others to mark utilities.
- 2. Place traffic control devices as needed.
- 3. Saw exterior limits of damaged section.
- 4. Remove damaged concrete, form, install steel, and place expansion felt at each transverse joint.
- 5. Pour concrete, finish, and apply curing compound.
- 6. When cured, remove forms, backfill, and seed.
- 7. Clean work area.
- 8. Remove traffic control devices.

SAFETY: Refer to the *Comprehensive Safety Program sharepoint portal*. Wear all appropriate PPE. Refer to the <u>Risk Based Assessment</u> for additional information.

OTHER CONSIDERATIONS: N/A

REFERENCES: Missouri Standard Specifications for Highway Construction Section; <u>609.10</u>.