Figure 616.18.3.3 Work Zone " Fine Sign and Speed Limit" Locations within the Advance Warning Area on a Multi-Lane Highway

SPEED	SIGN SPACING (ft.)	TAPER LENGTH (ft.)		RECOMMENDED	CHANNELIZER SPACING (ft.)	
Permanent Posted (mph)	Multi-Lane (S)	Shoulder (T1)	Lane (T2)	BUFFER LENGTH (ft.) (B)	Tapers	Buffer/ Work Areas
0-35	200	**This typical application provides guidelines for the sequencing and location of the work zone speed limit signs. Review appropriate typical applications for signs, sign spacing, taper length, buffer length, channelizer spacing, TMA's, channelizers, rumble strips, lights, etc.**				
40-45	500					
50-55	1000					
60-75	SA - 1000 SB - 1500 SC - 2640					

Notes:

For speed limit guidance, refer to EPG 616.18 Work Zone Speed Limits.

This typical application may be appropriate for work zone that may require a decrease of speed throughout the entire work zone.

(1) WO3-5 (SPEED LIMIT XX AHEAD). This sign is used only when the approved speed reduction for an immediate location is greater than 10 mph below the existing or posted speed limit.

(2) The speed limit sign may be moved upstream, if the district deems the work zone requires advance speed limit notification.

For undivided roadways, provide signs only on the right side of each direction.

Reduced speed limit signing shall be removed, covered, or turned from traffic when conditions requiring the reduced speed no longer exist.

SPEED LIMIT signs indicating the normal speed limit should be installed at the end of the reduced area provided no other reduction is imposed within the next one-half mile or no existing SPEED LIMIT sign is located within the next one-half mile.



