



- 1) NO OTHER DEVICES BESIDES THE LICENSE PLATE READER CAMERA AND SOLAR PANEL/BATTERY MAY BE MOUNTED SUPPORT POST
- 2) NO PORTION OF BREAKAWAY DEVICE FIXED TO THE GROUND SHALL BE MORE THAN 4" ABOVE FINISHED GRADE, SEE DETAIL A
- 3) THE INSTALLATION AND HARDWARE SHALL EXACTLY MATCH THE FLOCK SAFETY FLK2-4 BREAKAWAY INSTALLATION DETAILS DOCUMENT TO ASSURE THE ASSEMBLY IS INSTALLED AS IT WAS CRASH TESTED. THE 12'0" POLE LENGTH IS MEASURED FROM THE GROUND ON FLAT GRADES AND ON BACK SLOPES, IT IS MEASURED FROM THE EDGE OF DRIVING LANE / SHOULDER IN CASES WHERE THE GROUND SLOWS DOWN AWAY FROM THE ROADWAY
- 4) NO REMOTE BATTERY BOX MAY BE UTILIZED WITH THIS CONFIGURATION AS AN INSTALLATION OF THIS TYPE WAS NOT CRASH TESTED
- 5) INSTALLATIONS SHALL NOT BE PLACED ON SLOPES WITH GRADES STEEPER THAN 3:1
- 6) INSTALLATIONS SHALL NOT BE PLACED IN THE FLOW LINE OF DRAINAGE DITCHES
- 7) INSTALLATIONS SHALL NOT BE PLACED WITHIN 200 FEET OF ANY OTHER ROADWAY STRUCTURE

MODOT TYPICAL APPLICATION FOR FLOCK SAFETY FLK2-4 BREAKAWAY LPR INSTALLATION